

SNORKEL SR2755






MEASUREMENTS		METRIC	IMPERIAL
Working height maximum*		10.20 m	33 ft 6 in
A	Platform height maximum	8.40 m	27 ft 7 in
Platform dimensions (length x width)			
B x C	Standard	2.73 m x 1.40 m	9 ft x 4 ft 7 in
	Standard with extension	3.93 m x 1.40 m	13 ft x 4 ft 7 in
Slide-out platform extension deck		1.20 m	4 ft
Guardrail height		1.10 m	3 ft 7 in
Toeboard height		15 cm	6 in
D	Height - stowed	2.50 m	8 ft 2 in
	Height - stowed: rails folded	1.75 m	5 ft 9 in
E	Length - stowed	3.30 m	10 ft 10 in
F	Width	1.45 m	4 ft 9 in
G	Wheelbase	2 m	6 ft 7 in
H	Ground clearance - centre	26 cm	10 in
	Ground clearance - minimum	17 cm	7 in

PRODUCTIVITY		
Platform capacity	300 kg	660 lb
Slide-out platform extension deck capacity	120 kg	264 lb
Maximum number of persons - indoor / outdoor use	2 / 1	2 / 1
Maximum wind speed (12.5 m/s)	45 km/h	28 mph
Drive speed - below 2.40 m	7 km/h	4.35 mph
Drive speed - above 2.40 m	0.8 km/h	0.49 mph
Gradeability**	35%	19.29°
Inside turning radius	2.50 m	8 ft 2 in
Outside turning radius	4.75 m	15 ft 7 in
Exit / entry angle	20°	20°
Axle	articulating	articulating
Drive	four wheel	four wheel
Tyres - poly filled loader lug NHS	23x8.5-12	23x8.5-12
Wheel load maximum***	1,480 kgf	3,256 lbf

POWER	
Power source	Kubota diesel engine

WEIGHT****		
	2,580 kg	5,688 lb



*The metric equivalent of working height adds 2 m to platform height. Imperial adds 6 ft to platform height.

**Gradeability applies to driving on slopes. See operator's manual for details regarding slope rating.

***Floor loading information is approximate. It should be used only with adequate safety factors.

****Weight will vary depending on options.